Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier LaNe® Tech Härterpulver - Art. 82620

· Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:



Hafenstr. 83 - D-56564 Neuwied

Fon: +49(0)2631-3455-10 - Fax: +49(0)2631-3455-30 - Mail: service@w-r-lang.de Auskunftgebender Bereich: Produktsicherheit

Notrufnummern: Giftnotruf Mainz - 24 Stunden Notdienst - +49(0)6131-19240 Vergiftungsinformationszentrale der Gesundheit Österreich GmbH - +43(0)14064343

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 1B H360D May damage the unborn child.

H400 Aquatic Acute 1 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



· Signal word Danger

Hazard-determining

components of labelling:

dicyclohexyl phthalate dibenzoyl peroxide

Hazard statements

H242 Heating may cause a fire. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H360D May damage the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines).

P234 Keep only in original container. P264 Wash thoroughly after handling P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool. P420 Do not mix with peroxide-accelerators or reducing agents

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

· vPvB: Not applicable. (Contd. of page 1)

#### **SECTION 3: Composition/information on ingredients**

3.2 Chemical characterisation: Mixtures

| · Dangerous components:  |        |
|--|--------|
| CAS: 94-36-0<br>EINECS: 202-327-6<br>Index number: 617-008-00-0<br>Reg-No.: 01-2119511472-50 | 40-50% |
| CAS: 84-61-7<br>EINECS: 201-545-9<br>Index number: 607-719-00-4<br>Reg-No.: 01-2119978223-34 | 40-50% |
| · SVHC   |        |

84-61-7 dicyclohexyl phthalate

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

Protective equipment: Additional information Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.

Self-protection first!

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

(Contd. on page 3)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

(Contd. of page 2)

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Pick up mechanically, collect in a suitable receptacle and dispose in accordance with government

regulations.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

#### **SECTION 7: Handling and storage**

## 7.1 Precautions for safe

handling

Keep away from heat and direct sunlight. Open and handle receptacle with care.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

Oxidizing because of releasing oxygene. While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Dust can combine with air to form an explosive mixture.

Substance/product is oxidising when dry.

Product is not explosive. However, formation of explosive air/dust mixtures are possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

## · 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination. Storage in a collecting room is required.

Recommended storage temperature (To maintain

quality):

max.: +30 °C

7.3 Specific end use(s) No fur

No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

Additional information about

design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

(Contd. of page 3)

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

WEL (Great Britain) Long-term value: 5 mg/m³

84-61-7 dicyclohexyl phthalate

WEL (Great Britain) Long-term value: 5 mg/m³

· DNELs

94-36-0 dibenzoyl peroxide

Oral DNEL Longterm System 2 mg/kg bw/day (General population)

Dermal DNEL Longterm System 13.3 mg/kg bw/day (Worker)

Inhalative DNEL Longterm System 39 mg/m3 (Worker)

84-61-7 dicyclohexyl phthalate

Dermal DNEL Longterm System 0.5 mg/kg bw/day (Worker)
Inhalative DNEL Longterm System 35.2 mg/m3 (Worker)

· PNECs

94-36-0 dibenzoyl peroxide

PNEC Marinewater sed | 0.001 mg/kg sed dw | 0.00002 mg/l (AF 50) | PNEC Freshwater sed | 0.013 mg/kg sed dw |

PNEC STP 0.35 mg/l

PNEC Marinewater 0.000002 mg/l (AF 500)

84-61-7 dicyclohexyl phthalate

PNEC Marinewater sed 0.106 mg/kg sed dw PNEC Freshwater 0.004 mg/l (AF 50) 1.06 mg/kg sed dw PNEC Soil 0.21 mg/kg soil dw PNEC STP 10 mg/l (AF 10)

PNEC STP 10 mg/l (AF 10) PNEC Marinewater 0 mg/l (AF 500)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

• Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

The second secon

Filter P2

Protection of hands: Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye protection:

Tightly sealed goggles

(Contd. on page 5)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

Body protection:

Protective work clothing

(Contd. of page 4)

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

· General Information

Appearance:

Form:
Solid
Powder

Colour:
Whitish
Odour:
Characteristic
Not determined.

PH-value:
Not applicable.

· Change in condition

· Melting point/freezing point: Not applicable. · Initial boiling point and boiling range: Not applicable.

Flash point: Not applicable.Flammability (solid, gas): May cause fire.

Decomposition temperature: +60 °C (SADT)

• Explosive properties: Product is not explosive. However, formation of explosive air/dust mixtures are possible.

Product is not selfigniting.

· Explosion limits:

· Auto-ignition temperature:

Lower: Not determined.
 Upper: Not determined.
 Vapour pressure: Not applicable.

· **Density:** Not determined.

Bulk density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 610 kg/m³
 Not determined.
 Not applicable.
 Not applicable.

· Solubility in / Miscibility with

• water: Undetermined.

· Partition coefficient: n-octanol/water: not determined

Viscosity:

Dynamic: Not applicable.Kinematic: Not applicable.

9.2 Other information No further relevant information available.

• **Active oxygen** 3.2 - 3.5 %

## **SECTION 10: Stability and reactivity**

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: SADT (Self

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Self-accelerating decomposition at SADT. No further relevant information available.

10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

(Contd. on page 6)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

(Contd. of page 5)

Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

## **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

94-36-0 dibenzoyl peroxide

Oral LD50 >5,000 mg/kg (rattus)

84-61-7 dicyclohexyl phthalate

Oral LD50 >2,000 mg/kg (rattus)

Primary irritant effect: Skin corrosion/irritation

kin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin

sensitisation May cause an allergic skin reaction.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Reproductive toxicity May damage the unborn child.

STOT-single exposure
STOT-repeated exposure
Aspiration hazard
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

Aquatic toxicity:

94-36-0 dibenzoyl peroxide

EC50 / 72h | 0.0711 mg/l (pseudokirchneriella subcapitata)

LC50 / 96h 0.0602 mg/l (oncorhynchus mykiss)

EC50 / 48h 110 mg/l (daphnia magna)

12.2 Persistence and

degradability
No further relevant information available.

**Ecotoxical effects:** 

· Remark: Very toxic for fish

Additional ecological information:

General notes: Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable inert solid material to 10 %, the product must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

GB — (Contd. on page 7)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

(Contd. of page 6)

| SECTION 14: Transport information                          |   |
|--|---|
| · 14.1 UN-Number<br>· ADR, IMDG, IATA                      | UN3106  |
| · 14.2 UN proper shipping name<br>· ADR                    | 3106 ORGANIC PEROXIDE TYPE D, SOLID (DIBENZOYL<br>PEROXIDE), ENVIRONMENTALLY HAZARDOUS  |
| · IMDG   | ORGANIC PEROXIDE TYPE D, SOLID (DIBENZOYL PEROXIDE),<br>MARINE POLLUTANT<br>ORGANIC PEROXIDE TYPE D, SOLID (DIBENZOYL PEROXIDE) |
| · 14.3 Transport hazard class(es)                          | ONOANIOTEROXIDE TITE B, SOLIB (BIBLINZOTET ENOXIDE)   |
| · ADR  |   |
| ***************************************                    |   |
| · Class<br>· Label   | 5.2 (P1) Organic peroxides.<br>5.2  |
| · IMDG   |   |
|  |   |
| · Class<br>· Label   | 5.2 Organic peroxides.<br>5.2   |
| · IATA  · Class · Label                                    | 5.2 Organic peroxides.<br>5.2   |
| · 14.4 Packing group<br>· ADR, IMDG, IATA                  | Void  |
| 14.5 Environmental hazards:                                | Product contains environmentally hazardous substances: DIBENZOYL  |
| · Marine pollutant:  | PEROXIDE<br>Yes   |
| Special marking (ADR):                                     | Symbol (fish and tree) Symbol (fish and tree)   |
| 14.6 Special precautions for user                          | Warning: Organic peroxides.   |
| · Danger code (Kemler):<br>· EMS Number:                   | -<br>F-J,S-R  |
| 14.7 Transport in bulk according to Annex II of Marpo Code |   |
| Transport/Additional information:                          |   |
| ADR  |   |
| Limited quantities (LQ)                                    | 500 g<br>2  |
|  |   |
| Transport category Tunnel restriction code                 | D   |

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements

Qualifying quantity (tonnes) for

the application of upper-tier requirements

REGULATION (EC) No

1907/2006 ANNEX XVII

200 t

50 t

Conditions of restriction: 30

(Contd. on page 8)

Printing date 03.08.2018 Version: 10 Revision: 03.08.2018

Trade name: LaNe® Tech Härterpulver - Art. 82620

(Contd. of page 7)

· National regulations:

Other regulations, limitations and prohibitive regulations

Please note: Take care of the respective local regulations.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H360D May damage the unborn child. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Environment protection / Security of labour

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals GHS: Globally Harmonised System of classification and Labelling of Chemical SINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Org. Perox. B: Organic peroxides – Type B
Org. Perox. D: Organic peroxides – Type C/D
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the previous version altered.

GB